

SECTION 1. IDENTIFICATION

Product name: Energized Electrical Degreaser

Product code: 0321-3363 Product type: Aerosol.

Manufacturer: Quest Specialty Corporation, PO Box 624 Brenham, TX 77834 **National contact:** F4P, 11675 SW Tom Mackie Blvd, Port St. Lucie, FL 34987

Emergency telephone number of the company: 800-255-3924

SECTION 2. HAZARDS IDENTIFICATION

Classification of the CLASSIFICATION: Dissolved Gas

substance or mixture: Skin Irritant: Category 2

Eye Irritant: Category 2A

Specific Target Organ Toxicity (Single Exposure): Category 3

Carcinogenicity: Category 1B Germ Cell Mutagenicity: Category 2

GHS label elements Hazard pictograms







Signal Word:

Danger



SECTION 2. HAZARDS IDENTIFICATION

Hazard statements: DANGER: Contains gas under pressure; May explode if heated.

Causes skin and serious eye irritation. May cause drowsiness and dizziness.

May cause cancer.

Suspected of causing genetic defects.

This product contains the following percentage of chemicals of unknown toxicity: 0%

Precautionary statements

Prevention: Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on

an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50C/120F.

Response: Wash hands thoroughly after handling. If on skin: Wash with plenty of water. If skin irritation

occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, eye protection, and protective clothing. If exposed or

concerned: Get medical advice or attention.

Storage: Store locked up. Protect from sunlight. Store in a well-ventilated place.

Disposal: Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Supplemental label

elements:

Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison

center or doctor if you feel unwell.

Hazards not

otherwise classified

None known.



SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance/mixture: Mixture.

Other means of

Not available.

identification:

CAS number/other identifiers:

Ingredient name	% by weight	CAS number
Carbon Dioxide	3-7	124-38-9
Trichloroethylene	30-60	79-01-6
Tetrachloroethylene	30-60%	127-18-4

SECTION 4. FIRST AID MEASURES

Description of necessary first aid measures

Eye contact: Remove contact lenses. Flush with water for at least 15 minutes. See a physician if irritation

persists.

Inhalation: If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or

doctor if you feel unwell.

Skin contact: Immediately wash with soap and water for 15 minutes. Remove contaminated clothing and shoes

immediately. Seek medical attention if irritation persists.

Ingestion: Rinse mouth with water. Do not induce vomiting unless directed by medical authority. Seek

medical attention.



SECTION 4. FIRST AID MEASURES

Most important symptoms/effects, acute and delayed

Potential acute health effects:

Eye contact: Stinging, tearing, redness.

Skin contact: Prolonged or repeated contact may dry skin.

Ingestion: Vomiting, nausea, irritation.

CHRONIC HEALTH HAZARDS: Possible cancer causing agent and overexposure may also include damage to kidneys, liver, dizziness, headache, nausea, mental confusion, visual disturbances, dermatitis, lungs, blood, or central nervous system.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician: Do not administer adrenaline or epinephrine to a victim of chlorinated solvent poisoning. This

product contains ingredients that may be anticipated to be a carcinogen.



ERGIZED ELECTRICAL DEGREASER

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable

Use appropriate media for surrounding fire.

extinguishing

media:

None known.

extinguishing

Unsuitable

media:

Specific hazards

arising from the

chemical:

Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece

operated in a positive pressure demand mode with full body protective clothing when fighting fires.

Use water spray only to cool exposed containers.

Unusual Fire and

Contents under pressure. Exposure to temperatures above 120°F may cause

Explosion Hazards: bursting.

Hazardous

Combustion **Products:**

Oxides of carbon, chlorine, hydrogen chloride and phosgene.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel:

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non emergency personnel."

Environmental precautions:

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or

air).



SECTION 6. ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up

Spill: Use absorbent on spill, sweep to clean. Dispose in accordance with local, state and federal laws.

Small releases may be wiped up with wiping material.

Waste Dispose of in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap

Disposal: container and place in trash collection, do not puncture, incinerate, or reuse container.

RCRA Waste solvent likely considered U228 (Trichloroethylene), hazardous, under RCRA, however

Status: product should be fully characterized prior to disposal (40 CFR 261).

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

Protective Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding

measures: 50°C/122°F. Pressurized container: Do not pierce or burn, even after use. Store locked up.

Other Containers of this material may be hazardous when empty since they retain product residues

precautions: [vapors, liquid]; observe all warning and precautions listed for the product. Keep out of the reach of

children.

Conditions for Strong acids, strong alkalis, strong oxidizing agents, chemically active metals, such as aluminum,

safe storage, barium, lithium, sodium, magnesium, potassium, titanium, beryllium, concentrated nitric acid some

including any plastics, rubbers, and coatings.

incompatibilities:



SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	Exposure limits	
Carbon Dioxide	OSHA PEL	
	5000 ppm	
	ACGIH TLV	
	5000 ppm	
Trichloroethylene	OSHA PEL	
	10 ppm	
	ACGIH TLV	
	25 ppm	
Tetrachloroethylene	OSHA PEL	
	25 ppm	
	ACGIH TLV	
	100 ppm	



SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Material is heavier than air. Material may concentrate in low lying areas. Normal,

controls/ forced ventilation required to meet TLV requirements. Local exhaust ventilation is generally

ventilation: preferred.

Respiratory Wear NIOSH/MSHA approved organic vapor respiratory protection if used in confined, poorly

protective ventilated areas.

equipment

Additional Obtain special instructions before use. Do not handle until all safety precautions have been read

measures: and understood.



SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Aerosol

Appearance

Color: Not available.

Odor: Not available.

Odor threshold: Not available.

pH: Not available.

Melting point: Not available.

Boiling point: >188°F (87°C)

Flash point: Not available.

Evaporation rate: > 3 (Fast)

Flammability Not considered a flammable aerosol or **(solid, gas):** an extremely flammable Not available.

Not available.

Lower and upper

explosive (flammable)

limits:

Vapor pressure: (mm Hg): 59 Specific gravity: (H2O=1): 1.52

Solids: 0%

Vapor density:

[AIR=1]: > 2

Not available.

Not available.

>400°C

Vapor pressure: 1.44

Solubility: 0%

Partition

coefficient:

noctanol/ water:

Auto-ignition

temperature:

Decomposition

temperature:

Viscosity: Not available.

Molecular

weight:

Not applicable.

(Volts): 29,000

Dielectric strength:

Aerosol product

Type of aerosol: Spray

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Chemically active metals and acids

Chemical stability: The product is stable.

Possibility of None Known.

hazardous reactions:

Conditions to avoid: Temperatures greater than 122°F may cause bursting.

Incompatible Strong acids, strong alkalis, strong oxidizing agents, chemically active metals, such as aluminum,

materials: barium, lithium, sodium, magnesium, potassium, titanium, beryllium, concentrated nitric acid some

plastics, rubbers, and coatings.

Hazardous Oxides of carbon, chlorine, hydrogen chloride and phosgene.

decomposition

products:



ERGIZED ELECTRICAL DEGREASER

SECTION II. TOXICOLOGICAL INFORMATIO

Information on toxicological effects **Acute toxicity**

Trichloroethylene (79-01-6) LD50 (Oral, Rat) 5,650 mg/kg; Tumorigen, mutagenic reproductive effects in humans.

Tetrachloroethylene [127-18-4] LD50 [Oral, Rat] 2629 mg/kg; LD50 [Dermal, Rabbit] > 3228 mg/kg; LD50 [IPR, Mouse] 4700 mg/kg; LC50 (Inhalation, Mouse, 4hr) 5200 ppm; LC50 (Inhalation, Rat, 8hr) 34200 mg/m3

Routes of Eyes, Ingestion, Inhalation, Skin.

entry:

Eyes: Causes irritation, burning, redness, tearing.

Ingestion: Causes gastrointestinal irritation, headaches, nausea, diarrhea, vomitting, abdominal

cramps.

Inhalation: Irritation to respiratory tract, dizziness, headache, nausea, depression of central

nervous system, prolonged exposure may cause unconsciousness, heart effects, liver

effects, kidney effects, and death.

Skin: Irritation likely, redness and pain. May cause localized defatting, blistering with

prolonged skin contact. May be absorbed through the skin.

Medical Excessive exposure will aggravate pre-existing disorders of eyes, skin, respiratory, condition liver, kidney, cardiovascular system, pulmonary illnesses, or central nervous system.

aggravated:

Acute health Inhalation: dizziness, drowsiness, weakness, and fatigue

hazards: Eye: stinging, tearing, redness

Oral: Vomiting, nausea, irritation

Skin: Prolonged or repeated contact may dry skin

Chronic health Possible cancer causing agent and overexposure may also include damage to

hazards: kidneys, liver, dizziness, headache, nausea, mental confusion, visual disturbances,

dermatitis, lungs, blood, or central nervous system.

OSHA: Yes ACGIH: A2 - Suspected NTP: 2 - Anticipated Carcinogenicity:

IARC: 2A - Probable OTHER: CA Prop 65



SECTION 12. ECOLOGICAL INFORMATION

Ecological Trichloroethylene (79-01-6) LC50 (96hr) Fish: 10 and 100 mg/L. Slightly toxic to

information: aquatic life.

Biodegradability: Component or components of this product are not biodegradable.

Bioaccumulation: This product is not expected to bioaccumulate.

Soil mobility: This product is mobile in soil.

Other ecological hazards:

None known.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods: WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations. Do not dump

in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse

container.

RCRA STATUS: Waste solvent likely considered U228 (Trichloroethylene), hazardous, under RCRA,

however product should be fully

characterized prior to disposal (40 CFR 261).



ERGIZED ELECTRICAL DEGREASER

SECTION 14. TRANSPORT INFORMATION

Shipping: PROPER SHIPPING NAME: Aerosols, poison, Packing Group III, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.2 (6.1)

UN/NA NUMBER: UN 1950

PACKAGING GROUP: N/A\ AIR SHIPMENT

PROPER SHIPPING NAME: Forbidden

HAZARD CLASS/DIVISION: 2.2 (6.1)

UN/NA NUMBER: UN 1950

SHIPPING BY WATER:

VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols, Marine Pollutant

HAZARD CLASS/DIVISION: 2.2 (6.1)

UN/NA NUMBER: UN 1950

ENVIRONMENTAL HAZARDS WATER: Marine Pollutant







SECTION 15. REGULATORY INFORMATION

Tsca status: All Chemicals are listed or exempt.

Cercla Trichloroethylene (79-01-6)

(comprehensive Reportable Quantity = 100 lbs Tetrachloroethylene (127-18-4) Reportable Quantity = 100 lbs

response

compensation, and

liability act):

Sara 311/312 Acute Health, Chronic Health.

hazard categories:

Sara 313 reportable

ingredients:

Trichloroethylene (79-01-6) Tetrachloroethylene (127-18-4)

State regulations: Trichloroethylene (79-01-6) is known to the state of California to cause cancer.

Trichloroethylene (79-01-6) Right-to-Know acts for New York, Rhode Island, Pennsylvania, Florida, Minnesota, Massachusetts, Michigan, New Jersey, Tennesee; Spill Reporting for Massachusetts, New Jersey, Louisiana; Connecticut hazardous material survey; Illinois toxic

substances disclosure to employee act

International regulations:

Trichloroethylene, CAS 79-01-6, - EC - yes, Japan – yes, Australia – yes, Korea – yes, Canada DSL – yes, Canada NDSL –no, Philipenes – yes. Tetrachloroethylene (127-18-4) WHMIS

[Canada] Class D-1B: Material causing immediate and serious toxic effects [TOXIC]. Class D-2A:

Material causing other toxic effects (VERY TOXIC).

NFPA HEALTH: 2 HMIS HEALTH: 2

NFPA FLAMMABILITY: 1
NFPA REACTIVITY: 0
HMIS REACTIVITY: 0
NFPA OTHER: None
HMIS PROTECTION: C



SECTION 14. ADDITIONAL INFORMATION

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.